



1
2
3

Project	ZigBee Alliance		
---------	-----------------	--	--

Title	SEP 1.1 PICS		
-------	---------------------	--	--

Date Submitted	[5 April 2011]		
----------------	----------------	--	--

Source	[Rob Alexander] [Ember, Inc.] [25 Thomson Place Boston, MA 02210]	Voice:	[617-951-1244]
		Fax:	[]
		E-mail:	[rob.alexander@ember.com]

Re:	[095311r17 (PICS) and 095312r30 (Test)]		
-----	---	--	--

Abstract	[This document lists PICS for Smart Energy Profile]		
----------	---	--	--

Purpose	[Provides a list of changes that are applied to the ZigBee SE 1.1 Profile Specification revision 16, PICS and Test specification. The changes will be incorporated into a future release of the specification.]		
---------	---	--	--

Notice	This document has been prepared to assist the ZigBee Alliance. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.		
--------	--	--	--

Release	The contributor acknowledges and accepts that this contribution will be posted in the member area of the ZigBee web site.		
---------	---	--	--

4
5

1

Legal
Notice

Copyright © ZigBee Alliance, Inc. All rights Reserved. This information within this document is the property of the ZigBee Alliance and its use and disclosure are restricted.

Elements of ZigBee Alliance specifications may be subject to third party intellectual property rights, including without limitation, patent, copyright or trademark rights (such a third party may or may not be a member of ZigBee). ZigBee is not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

This document and the information contained herein are provided on an “AS IS” basis and ZigBee DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO (A) ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OF THIRD PARTIES (INCLUDING WITHOUT LIMITATION ANY INTELLECTUAL PROPERTY RIGHTS INCLUDING PATENT, COPYRIGHT OR TRADEMARK RIGHTS) OR (B) ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE OR NON-INFRINGEMENT. IN NO EVENT WILL ZIGBEE BE LIABLE FOR ANY LOSS OF PROFITS, LOSS OF BUSINESS, LOSS OF USE OF DATA, INTERRUPTION OF BUSINESS, OR FOR ANY OTHER DIRECT, INDIRECT, SPECIAL OR EXEMPLARY, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY KIND, IN CONTRACT OR IN TORT, IN CONNECTION WITH THIS DOCUMENT OR THE INFORMATION CONTAINED HEREIN, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE. All Company, brand and product names may be trademarks that are the sole property of their respective owners.

The above notice and this paragraph must be included on all copies of this document that are made.

ZigBee Alliance, Inc.
2400 Camino Ramon, Suite 375
San Ramon, CA 94583

2

Table of Contents

1 Table of Contents3

2 References.....5

3 1.1 ZigBee Alliance documents5

4 1.2 IEEE documents5

5 1.3 ISO documents5

6 Change history6

7 Revision 0 (November, 2007)7

8 2 Introduction.....9

9 2.1 Scope.....9

10 2.2 Purpose.....9

11 3 Abbreviations and special symbols10

12 4 Instructions for completing the PICS proforma11

13 5 Identification of the implementation12

14 6 Identification of the protocol.....14

15 7 Global statement of conformance15

16 8 PICS proforma tables.....16

17 8.1 ZigBee Device Types16

18 8.2 Stack Profile16

19 8.3 Stack Profile extensions for SE17

20 8.4 SE general requirements support17

21 8.5 ZigBee SE device description support20

22 8.6 SE common clusters.....21

23 8.7 ZigBee SE Device Description Capabilities25

24 8.7.1 Energy Service Interface device functions.....25

25 8.7.2 Metering device functions.....26

26 8.7.3 In-Premises display device functions.....27

27 8.7.4 Programmable Communicating Thermostat (PCT) device functions28

28 8.7.5 Load Control device functions.....29

29 8.7.6 Range Extender device functions30

30 8.7.7 Smart Appliance device functions31

31 8.7.8 Prepayment Terminal device functions.....32

32 8.8 Smart Energy Application Specific Cluster function capabilities.....33

33 8.8.1 Basic Cluster33

34 8.8.2 Identify.....33

35 8.8.3 Alarms33

36 8.8.4 Commissioning.....33

37 8.8.5 Power Configuration34

38 8.8.6 Time Cluster attributes and functions.....34

39 8.8.7 Key Establishment Cluster attributes and functions35

40 8.8.8 Demand Response and Load Control Cluster attributes and functions36

41 8.8.9 Metering Cluster attributes and functions.....37

42

1	8.8.10	Price Cluster attributes and functions.....	47
2	8.8.11	Messaging Cluster attributes and functions	50
3	8.8.12	Tunneling Cluster attributes and functions	51
4	8.8.13	Prepayment Cluster attributes and functions.....	53
5	8.8.14	Trust Center Swap-out	55
6	8.8.15	Multiple ESI.....	56
7	8.8.16	OTA Upgrade Cluster attributes and functions.....	57
8	8.8.17	Support on Non SE clusters	58
9			

References

The following standards contain provisions, which, through reference in this document, constitute provisions of this standard. All the standards listed are normative references. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

1.1 ZigBee Alliance documents

- [R1] ZigBee document 053474r18: ZigBee Specification 2007
- [R2] ZigBee document 105638r09: ZigBee Smart Energy Profile Specification Revision 16
- [R3] ZigBee document 075123r03, ZigBee Cluster Library Specification
- [R4] ZigBee document 04300r08: ZigBee Network Layer PICS
- [R5] ZigBee document 064147r07: ZigBee Application Layer PICS
- [R6] ZigBee document 043171r04: ZigBee Security Layer PICS
- [R7] ZigBee document 064113r07: ZigBee Cluster Library PICS
- [R8] ZigBee document 08006r03: ZigBee 2007 Layer PICS and Stack Profiles
- [R9] ZigBee document number 095264r03: ZigBee OTA Upgrade Cluster Specification
- [R10] ZigBee document number 095284r06: ZigBee OTA Upgrade Cluster PICS

1.2 IEEE documents

- [R11] IEEE Standard for Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) specifications for Low Rate Wireless Personal Area Networks (LR-WPANs), 2003.

1.3 ISO documents

- [R12] ISO/IEC 9646-1:1991, Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts.
- [R13] ISO/IEC 9646-7:1995, Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7. Implementation conformance statements.

1 **Change history**

2 The following table shows the change history for this specification.

1 **Revision 0 (November, 2007)**

2

Table 1 – Revision change history for revision 0

Revision	Version	Description
R00	-	Initial draft
R01	-	Updated to Revision 12 of the SE specification and Errata.
R02	-	Updated to Revision 14 of the SE specification
R03	-	Fix typo. Update SE specification reference to r14.
R04		Update SE specification reference to r15. Update section references.
R05	-	Use 2009 ZB template Change AMI to SE item numbers and headings R15 CCBs: CCB 940 Rename Simple Metering to Metering CCB 1011 Update reference CCB 1012 Time cluster optional for Range Extender CCB 1013 Clarify AMG3 CCB 1042 PICS item number conflict between SE and ZCL CCB 1120 Install Codes CCB 1130 Binding and Service Discovery
R06	0.7	0.7 LB Passed
R07	0.9	Initial 0.9 draft Develco CCBs 1179 and 1181 Merge r15 Errata CCBs
R08		
R09	0.9	Update from SE 1.1 CCB Review
R11	0.9	Added Request Fast Polling Items Added Publish Block Period Items Added Get Block Period(s) Items Replaced out of date tunneling Items Marked SEG27 as Mandatory.
R12	0.9	Removed outdated common clusters. Updated Document reference [R2]

		Add Trust Center Swap-Out parameter, unified item number format
R13		Suggested new wording in Tables 8, 10, 14, 16, 18, 22 & 24 Changes to Price Cluster entries (8.8.10)
R14	0.9	Removed references to DIAG and CM clusters. Clarified SEG3 requirement regarding attribute reporting.
R15	0.9	Add changes from SE1.1 Inter-op event Add editorial changes: Title change to SEP 1.1 Intermediate Release PICS Draft Header - Change date to Oct 6 2010 Header - change release to R15 (to include these changes and Jeff's below) Date Submitted Oct 6 2010 Source - Ben and Ben's address Remove Footer – Author and replace with company name submitting PICS Update [R2] Reference to latest SE1.1 Spec - 105638r09 or r10 if you are going to release r09 with changes. Add reference [R10] 095284r06 OTA Upgrade Cluster PICS Page 57 line 6 - If supporting OTA upgrade cluster client or server, need to complete OTA Upgrade Cluster PICS document in addition to this document for certification.
R16	1.0	Add change to support multiple instances of cluster functions via multiple end point tracking Add tracking by end point in replies for clusters supported Add support for non SE clusters to allow tracking in PICS plus certification
R17	1.0	Title changed to remove “Intermediate” and “Draft”. Document format changed from WBK to DOC. Updated Document numbers and revision number.

2 Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a given standard. Such a statement is called a protocol implementation conformance statement (PICS).

2.1 Scope

This document provides the protocol implementation conformance statement (PICS) proforma for the ZigBee specifications cited in Reference [R2] in compliance with the relevant requirements, and in accordance with the relevant guidance, given in ISO/IEC 9646-7.

This document addresses the ZigBee SE Application Profile.

2.2 Purpose

The supplier of a protocol implementation claiming to conform to the ZigBee SE Application Profile shall complete the following PICS proforma and accompany it with the information necessary to identify fully both the supplier and the implementation.

The PICS is in the form of answers to a set of questions in the PICS proforma. The questions in a proforma consist of a systematic list of protocol capabilities and options as well as their implementation requirements. The implementation requirement indicates whether implementation of a capability is mandatory, optional, or conditional depending on options selected. When a protocol implementer answers questions in a PICS proforma, they would indicate whether an item is implemented or not, and provide explanations if an item is not implemented.

3 Abbreviations and special symbols

Notations for requirement status:

M	Mandatory
O	Optional
O.n	Optional, but support of at least one of the group of options labeled O.n is required.
N/A	Not applicable
X	Prohibited
<i>Item Number</i> : : <i>Status</i>	Status is conditional on support of item number

“*Item Number*”: Conditional, status dependent upon the support marked for the “*Item Number*”.

For example, FD1: O.1 indicates that the status is optional but at least one of the features described in FD1 is required to be implemented, if this implementation is to follow the standard of which this PICS Proforma is a part.

4 Instructions for completing the PICS proforma

- 1
- 2
- 3 If a given implementation is claimed to conform to this standard, the actual PICS proforma to be
- 4 filled in by a supplier shall be technically equivalent to the text of the PICS proforma in this annex,
- 5 and shall preserve the numbering and naming and the ordering of the PICS proforma.
- 6
- 7 A PICS which conforms to this document shall be a conforming PICS proforma completed in
- 8 accordance with the instructions for completion given in this annex.
- 9
- 10 The main part of the PICS is a fixed-format questionnaire, divided into five tables. Answers to the
- 11 questionnaire are to be provided in the rightmost column, either by simply marking an answer to
- 12 indicate a restricted choice (such as Yes or No), or by entering a value, set, or range of values.

5 Identification of the implementation

Implementation under test (IUT) identification

IUT name: REX2 / gREX Meter

IUT version:

5.5

System under test (SUT) identification

SUT name: REX2 / gREX Meter with ZigBee option

Software Version: App 5.5 and Radio 5.4 (both REX2 / gREX)

Hardware Version: REX2 and gREX (same HW design different form factor)

Operating system (optional):

Product supplier

Name: Elster Solutions, LLC

Address: 208 South Rogers Lane Raleigh NC 27610

Telephone number: 1-800-338-5251

Facsimile number: 1-919-212-4801

Email address: info@us.elster.com

1 Additional information: _____
2
3

4 **Client**

5
6 Name: Robert Henes _____
7

8 Address: 208 South Rogers Lane Raleigh NC 27610 _____
9
10 _____
11

12 Telephone number: 1-919-212-4817 _____
13

14 Facsimile number: 1-919-212-4801 _____
15

16 Email address: Robert.J.Henes@us.elster.com
17

18 Additional information: _____
19
20

21 **PICS contact person**

22
23 Name: Mark Ranta _____
24

25 Address: 208 South Rogers Lane Raleigh NC 27610 _____
26
27 _____
28

29 Telephone number: 1-919-212-4869
30 _____
31

32 Facsimile number: 1-919-250-5439
33 _____
34

35 Email address: Mark.Ranta@us.elster.com _____
36

37 Additional information: _____
38
39

40
41 **PICS/System conformance statement**
42

1 **6 Identification of the protocol**

2

3 This PICS proforma applies to ZigBee SE Application Profile, cited in Reference [R2].

7 Global statement of conformance

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18

The implementation described in this PICS proforma meets all of the mandatory requirements of the referenced standards:

Application Profile: ZigBee SE – 075356r16

Yes

No

Note -- Answering ‘No’ indicates non-conformance to the specified protocol standard. Non-supported mandatory capabilities are to be identified in the following tables, with an explanation by the implementer explaining why the implementation is non-conforming.

The supplier will have fully complied with the requirements for a statement of conformance by completing the statement contained in this sub-clause. That means, by clicking the above, the statement of conformance is complete.

8 PICS proforma tables

The following tables are composed of the detailed questions to be answered, which make up the PICS proforma.

8.1 ZigBee Device Types

Table 2 - Functional device types

Item number	Item description	Reference	Status	Support
FDT1	Is this device capable of acting as a ZigBee coordinator?	[R1]/2.5.5.5.1	¹ O.1	Yes
FDT2	Is this device capable of acting as a ZigBee router?	[R1]/2.5.5.5.2	O.1	No
FDT3	Is this a ZigBee end device?	[R1]/2.5.5.5.3	O.1	No

8.2 Stack Profile

Table 3 –Stack Profile

Item number	Item description	Reference	Status	Support
ZSP1	Is the device built on a ZigBee Compliant Platform certified for the ZigBee stack profile [R8]?	[R4] [R2]/5.2	O.2 ²	No
ZSP2	Is the device built on a ZigBee PRO Compliant Platform certified for the ZigBee PRO stack profile [R8]?	[R8] [R2]/5.2	O.2	Yes

¹ O.1 – Device under test must select only one of these options. Devices under test supporting multiple ZigBee device types must serially re-test using each supported ZigBee device type.

² O.2 – Device under test must be deployed on either of the ZigBee or ZigBee PRO stack profiles.

1 **8.3 Stack Profile extensions for SE**

2 **Table 4 – Stack profile extensions for SE**

Item number	Item description	Reference	Status	Support
SPE1	Does the device support Application Link Keys?	[R2]/5.2 [R6]/ASLS6	M	Yes
SPE2	Does this device use a stack that supports fragmentation?	[R2]/5.2 [R5]/ADF5, ADF6	M	Yes
SPE3	Does this device use any SE Profile Commands that require the use of Fragmentation?	[R2]/5.2 [R5]/ADF5, ADF6	MC1: M MS1: M	Yes
SPE4	Does the device adhere to the polling rate specifications given in [R2]/5.2 (i.e. Does your application poll equal to or less often as called out in the specification)?	[R2]/5.2	FDT3:M	NA
SPE5	Does this devices support reception of fragmented messages?		M	Yes
SPE6	Does this device support generation of fragmented messages?		O	Yes

3
4 **8.4 SE general requirements support**

5 In the below tables please answer Yes / No for supported , number of instances supported, and
6 end point for each instance. In support one instance can just provide end point number without
7 instance number.

8 **Table 5 – SE general requirements support**

Item number	Item description	Reference	Status	Support
SEG1	Does the device support the ZigBee Cluster Library?	[R2]/5.10, 5.11 [R3]	M	Yes

Item number	Item description	Reference	Status	Support
SEG2	Does the device support the ZigBee Cluster Library List specified for SE including the mandatory/optional clusters detailed in the ZCL PICs?	[R2]/5.10, 5.11 [R7]	M	Yes
SEG3	Does the device support the ZigBee Cluster Library with the parameters for attribute reporting, reporting configuration and read reporting configuration as detailed in the SE Profile clusters? Editor's Note: Reporting interval constraints and other parameters are mandatory where attribute reporting is used. Support of attribute reporting may be optional or mandatory based on clusters implemented.	[R2]/5.11 [R3]	M	Yes
SEG4	Is the device capable of joining a ZigBee SE network and does it interact with a consumer ZigBee Home Area Network only through a bridge device?	[R2]/5.1	FDT2: M FDT3: M	NA
SEG5	Does the device support "E-Mode" commissioning? SE Profile requirement: Those devices that will join an existing network must support button pushes or simple documented user interfaces to initiate the joining process.	[R2]/5.1	FDT2: M FDT3: M For joining devices	NA
SEG6	Deleted	[R2]/5.1		N/A
SEG7	Does the device support the compatible Startup Attribute Set, Join Parameters, Security Parameters, End Device Parameters, Link Status Parameters, Concentrator Parameters, APS Transport Parameters and Binding Parameters?	[R2]/5.3, 5.3.1, 5.3.2, 5.3.3, 5.3.4, 5.3.5, 5.3.6, 5.3.7, 5.3.8, 5.3.9	M	Yes
SEG8	Does the device support joining with pre-installed link keys? Note: SE specifies use of Install Codes to derive the link key.	[R2]/5.4.1	FDT2: M FDT3: M	NA

Item number	Item description	Reference	Status	Support
SEG9	Does the device support joining using the key establishment cluster?	[R2]/5.4.7	FDT2: M FDT3: M	NA
SEG10	Deleted	[R2]/5.5		NA
SEG11	Does the device support the list of SE preferred channels?	[R2]/5.8.1	O	Yes
SEG12	Does the device support the SE broadcast policy?	[R2]/5.8.2	O	Yes
SEG13	Does the device support the SE frequency agility policy?	[R2]/5.8.3	O	Yes
SEG14	Does the device support the security key update policies for SE networks?	[R2]/5.8.4	M	Yes
SEG15	Does the device support the ZCL Time Cluster and SE time synchronization? Editor's Note: Support of the ZCL Time Cluster is not mandatory for all SE devices. The SE device descriptions define the required Time cluster support.	[R2]/5.12.1.1	O	Yes
SEG16	Does the device support discovery of optional attributes?	[R2]/5.12	M	Yes
SEG17	Does the device application discover and handle unsupported attributes in other devices?	[R2]/5.12	M	Yes
SEG18	Does the device support an indication to the user that the network has formed properly?	[R2]/5.5.1	O	Yes via logs available to head end
SEG19	Does the device support an indication to the user that a device has joined a network successfully?	[R2]/5.5.1	O	Yes via logs available to head end
SEG20	Does the device support the commissioning modes and provide supporting commissioning	[R2]/5.5.2, 5.5.3, 5.5.4	M	Yes

Item number	Item description	Reference	Status	Support
	documentation according to network type?			
SEG21	Does the device use the appropriate security key per cluster?	[R2]/5.4.6	M	Yes
SEG22	Does the device support the SE Mirrored Device Capacity – Service Discovery?	[R4]/5.8.5	O	No
SEG23	Does one of the device support the SE Install Code Formats: 48, 64, 96, or 128 bit number and 16 bit CRC?	[R4]/5.4.8.1.1	O	Yes
SEG24	Does the device expect to receive unsolicited messages from the DRLC, Messaging, Metering or Pricing clusters?	[R4]/5.4.5.1	O	Yes
SEG25	Does the device support rejoining a secured network?	[R4]/5.4.2	M	Yes
SEG26	Does the device support devices leaving its network?	[R4]/5.4.3	FDT1:M	Yes
SEG27	Does the device support updating the Network Key?	[R4]/5.4.4	M	Yes
SEG28	Does the device support updating the Link Key?	[R4]/5.4.5	M	Yes

1 **8.5 ZigBee SE device description support**

2 **Table 6 – SE device description support**

Item number	Item description	Reference	Status	Support
SED1	Is the product programmed as an Energy Service Interface?	[R2]/6.3.1	O.3 ³	Yes 1 EP#10H
SED2	Is the product programmed as a Metering Device?	[R2]/6.3.2	O.3	No

³ O.3 – Device under test must select at least one and may select more than one of the SE device descriptions. If multiple SE device descriptions are supported in the same device then each of the supported device descriptions must be deployed on individual endpoints within the device under test.

Item number	Item description	Reference	Status	Support
SED3	Is the product programmed as an In-Premises Display?	[R2]/6.3.3	O.3	No
SED4	Is the product programmed as a Programmable Communicating Thermostat (PCT)?	[R2]/6.3.4	O.3	No
SED5	Is the product programmed as a Load Control?	[R2]/6.3.5	O.3	No
SED6	Is the product programmed as a Range Extender?	[R2]/6.3.6	O.3	No
SED7	Is the product programmed as a Smart Appliance?	[R2]/6.3.7	O.3	No
SED8	Is the product programmed as a Prepayment Terminal?	[R2]/6.3.8	O.3	No

1
2
3
4
5
6

8.6 SE common clusters

The common cluster ZCL PICs restrictions/requirements are obtained from [R2]/5.11, 5.12.

Table 7 – Common cluster ZCL PICs restrictions/requirements

ZCL PICs Item number [R7]	Status	Additional Constraints	Support
FC100	M	ZCL Cluster ID enumeration is mandatory	Yes
FC1	M	General ZCL Frame Format is mandatory	Yes
BCC1	O	Does the device support the Basic Cluster as a client?	No
BCS1	M	Does the device support the Basic Cluster as a server?	Yes 1 – EP#10H
GCC1	O	Deleted	NA
GCS1	O	Deleted	NA

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
ACC1	O	Does the device support the Alarms Cluster as a client?	No
ACS1	O	Does the device support the Alarms Cluster as a server?	No
TCS1		Deleted	NA
TCC1		Deleted	NA

1
2

Table 8 – Common cluster support

Item number	Item description	Reference	Status	Support
ASDC1	Deleted	[R2]/5.10		NA
ASDC2	Deleted	[R2]/5.10		NA
ASDC3	Deleted	[R2]/5.10		NA
ASDS1	Deleted		O	NA
ASDS2	Does the device support the server Price Cluster sent via the Anonymous Inter-PAN transmission mechanism?	[R2]/Annex D.4	O	No
ASDS3	Does the device support the server Messaging Cluster sent via the Anonymous Inter-PAN transmission mechanism?	[R2]/Annex D.5	O	No
KEC1	Does the device support the Key Establishment cluster as a client?	[R2]/Annex C.3.1	M	Yes
KES1	Does the device support the Key Establishment cluster as a server?	[R2]/Annex C.3.1	FDT1:M FDT2:M FDT3:O	Yes

Item number	Item description	Reference	Status	Support
PC1	Does the device support the Price cluster as a client?	[R2]/6.1	O	No
PS1	Does the device support the Price cluster as a server?	[R2]/ 6.1	O	Yes
DRLC1	Does the device support the Demand Response and Load Control cluster as a client?	[R2]/ 6.1	O	No
DRLS1	Does the device support the Demand Response and Load Control cluster as a server?	[R2]/ 6.1	O	Yes 1 – EP#10H
SMC1	Does the device support the Metering cluster as a client?	[R2]/ 6.1	O	No
SMS1	Does the device support the Metering cluster as a server?	[R2]/ 6.1	O	Yes 1 – EP#10H
MC1	Does the device support the Messaging cluster as a client?	[R2]/ 6.1	O	No
MS1	Does the device support the Messaging cluster as a server?	[R2]/ 6.1	O	Yes 1 – EP#10H
PPC1	Does the device support the Prepayment cluster as a client?	[R2]/ 6.1	O	No
PPS1	Does the device support the Prepayment cluster as a server?	[R2]/ 6.1	O	No
SECC1	Does the device support clusters with Reporting Capability?	[R2]/6.1.1	O	No
SECC2	Are any manufacturer-specific cluster(s) supported?	[R2]/6.1.2	O	No
SECC3	Are any non-SE ZCL or other application cluster(s) supported?	[R2]/6.1.3	O	No
ICS1	Does the device support the Identify cluster?	[R2]/ 6.1	O	No
PCCS1	Does the device support the Power	[R2]/ 6.1	O	No

Item number	Item description	Reference	Status	Support
	Configuration cluster?			
SMC2	Does the device support the Block Tariffs Metering cluster attributes as a client?	[R2]/ 6.1	O	No
SMS2	Does the device support the Block Tariffs Metering cluster attributes as a server?	[R2]/ 6.1	O	No
TUC1	Does the device support the Tunneling cluster as a client?	[R2]/ 6.1	O	No
TUS1	Does the device support the Tunneling cluster as a server?	[R2]/ 6.1	O	No
TCSW1	Does the device support Trust Center Swap-out ?	[R2]/ 6.1	O	No
OTAC1	Does the device support the OTA Upgrade cluster as a client?	[R2]/ 6.1	O	No
OTAS1	Does the device support the OTA Upgrade cluster as a server?	[R2]/ 6.1	O	No
ALM1	Does the device support the Alarms as a server?	[R2]/ 6.1	O	No

1
2

8.7 ZigBee SE Device Description Capabilities

Tables in the following sub-clauses detail the capabilities specific to a device description.

8.7.1 Energy Service Interface device functions

Table 9 – Energy Service Interface ZCL PICS restrictions/requirements

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
TCS1	M	Time Cluster server is mandatory	Yes 1 – EP#10H

Table 10 provides the SE PICS restrictions based on requirements in [R2]/6.3.1.1.

Table 10 – Energy Service Interface SE PICS restrictions/requirements

SE PICS Item number	Status	Additional Constraints	Support
SMC1	O	Metering Cluster client is optional	No
SMS1	O	Metering Cluster server is optional	Yes 1 – EP#10H
MS1	M	Messaging Cluster server is mandatory	Yes 1 – EP#10H
PS1	M	Price Cluster server is mandatory	Yes 1 – EP#10H
DRLS1	M	Demand Response and Load Cluster server is mandatory	Yes 1 – EP#10H
PC1	O	Price Cluster client is optional	No
MS1	O	Messaging Cluster client is optional	No
PPC1	O	Prepayment Cluster client is optional	No

SE PICS Item number	Status	Additional Constraints	Support
PPS1	O	Prepayment Cluster server is optional	No
TUS1	O	Tunneling Cluster server is optional	No
TCSW1	O	Trust Center Swap-out is optional	No
OTAS1	O	OTA Upgrade Cluster server is optional	No
TUC1	O	Tunneling Cluster client is optional	No
OTAC1	O	OTA Upgrade Cluster client is optional	No

1
2
3

4 **8.7.2 Metering device functions**

5 **Table 11 – Metering device ZCL PICS restrictions/requirements**

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
TCC1	O	Time Cluster client is optional	NA

6
7
8
9

Table 12 provides the SE PICs restrictions based on requirements in [R2]/6.3.2.1.

Table 12 – Metering device SE PICS restrictions/requirements

SE PICS Item number	Status	Additional Constraints	Support
SMS1	M	Metering Cluster server is mandatory	[NA]
PPS1	O	Prepayment Cluster server is optional	NA
PC1	O	Price Cluster client is optional	NA

SE PICS Item number	Status	Additional Constraints	Support
MC1	O	Messaging Cluster client is optional	NA
SMS2	O	Block Tariffs Metering cluster server attributes are optional	NA
TUC1	O	Tunneling Cluster client is optional	NA
TUS1	O	Tunneling Cluster server is optional	NA
TCSW1	O	Trust Center Swap-out is optional	NA
OTAC1	O	OTA Upgrade Cluster client is optional	NA
OTAS1	O	OTA Upgrade Cluster server is optional	NA

1

2 **8.7.3 In-Premises display device functions**

3

Table 13 – In-Premises display device ZCL PICS restrictions/requirements

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
TCC1	O	Time Cluster client is optional	NA

4

5 Table 14 provides the SE PICS restrictions based on requirements in [R2]/6.3.3.1.

6

7

Table 14 – In-Premises display device SE PICS restrictions/requirements

SE PICS Item number	Status	Additional Constraints	Support
DRLC1	O	Demand Response and Load Cluster client is optional	NA
PC1	O	Price Cluster client is optional	NA

SE PICS Item number	Status	Additional Constraints	Support
SMC1	O	Metering Cluster client is optional	NA
PPC1	O	Pre-payment Cluster client is optional	NA
MC1	O	Messaging Cluster client is optional	NA
TUC1	O	Tunneling Cluster client is optional	NA
TCSW1	O	Trust Center Swap-out is optional	NA
OTAC1	O	OTA Upgrade Cluster client is optional	NA
OTAS1	O	OTA Upgrade Cluster server is optional	NA

1
2
3

8.7.4 Programmable Communicating Thermostat (PCT) device functions

Table 15 Programmable Communicating Thermostat (PCT) ZCL PICS restrictions/requirements

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
TCC1	M	Time Cluster client is mandatory	NA

6
7
8
9

Table 16 provides the SE PICS restrictions based on requirements in [R2]/6.3.4.1.

Table 16 Programmable Communicating Thermostat (PCT) SE PICS restrictions/requirements

SE PICS Item number	Status	Additional Constraints	Support
DRLC1	M	Demand Response and Load Cluster client is mandatory	NA

SE PICS Item number	Status	Additional Constraints	Support
PPC1	O	Prepayment Cluster client is optional	NA
PPC1	O	Pre-payment Cluster client is optional	[NA]
PC1	O	Price Cluster client is optional	NA
SMC1	O	Metering Cluster client is optional	NA
MC1	O	Messaging Cluster client is optional	NA
TUC1	O	Tunneling Cluster client is optional	NA
TCSW1	O	Trust Center Swap-out is optional	NA
OTAC1	O	OTA Upgrade Cluster client is optional	NA
OTAS1	O	OTA Upgrade Cluster server is optional	NA

1

2 **8.7.5 Load Control device functions**

3

Table 17 – Load Control ZCL PICS restrictions/requirements

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
TCC1	M	Time Cluster client is mandatory	NA

4

5 Table 18 provides the SE PICS restrictions based on requirements in [R2]/6.3.5.1.

6

7

Table 18 – Load Control SE PICS restrictions/requirements

SE PICS Item number	Status	Additional Constraints	Support
DRLC1	M	Demand Response and Load Cluster client is mandatory	NA

SE PICS Item number	Status	Additional Constraints	Support
PC1	O	Price Cluster client is optional	NA
TUC1	O	Tunneling Cluster client is optional	NA
TCSW1	O	Trust Center Swap-out is optional	NA
OTAC1	O	OTA Upgrade Cluster client is optional	NA
OTAS1	O	OTA Upgrade Cluster server is optional	NA

1

2 **8.7.6 Range Extender device functions**

2

3

Table 19 – Range Extender ZCL PICS restrictions/requirements

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
TCC1	O	Time Cluster client is optional.	NA

4

5 Table 20 provides the SE PICS restrictions based on requirements in [R2]/6.3.6.1.

6

7

Table 20 –Range Extender SE PICS restrictions/requirements

SE PICS Item number	Status	Additional Constraints	Support
TCSW1	O	Trust Center Swap-out is optional	NA
OTAC1	O	OTA Upgrade Cluster client is optional	NA
OTAS1	O	OTA Upgrade Cluster server is optional	NA

8

1 **8.7.7 Smart Appliance device functions**

2 **Table 21 – Smart Appliance ZCL PICS restrictions/requirements**

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
TCC1	M	Time Cluster client is mandatory	NA

3
4 Table 22 provides the SE PICS restrictions based on requirements in [R2]/6.3.7.1.

6 **Table 22 –Smart Appliance SE PICS restrictions/requirements**

SE PICS Item number	Status	Additional Constraints	Support
PPC1	O	Prepayment Cluster client is optional	NA
DRLC1	O	Demand Response and Load Cluster client is optional	NA
PC1	M	Price Cluster client is mandatory	NA
SMC1	O	Metering Cluster client is optional ED NOTE: This is not listed in the specification – should it be?	NA
MC1	O	Messaging Cluster client is optional	NA
TUC1	O	Tunneling Cluster client is optional	NA
TCSW1	O	Trust Center Swap-out is optional	NA
OTAC1	O	OTA Upgrade Cluster client is optional	NA
OTAS1	O	OTA Upgrade Cluster server is optional	NA

7
8

1 **8.7.8 Prepayment Terminal device functions**

2 **Table 23 – Prepayment Terminal ZCL PICS restrictions/requirements**

ZCL PICS Item number [R7]	Status	Additional Constraints	Support
TCC1	M	Time Cluster client is mandatory	NA

3
4 Table 24 provides the SE PICS restrictions based on requirements in [R2]/6.3.8.1.

5
6 **Table 24 – Per-payment Terminal SE PICS restrictions/requirements**

SE PICS Item number	Status	Additional Constraints	Support
DRLC1	O	Demand Response and Load Cluster client is optional	NA
PC1	M	Price Cluster client is mandatory	NA
SMC1	O	Metering Cluster client is optional	NA
MC1	O	Messaging Cluster client is optional	NA
TUC1	O	Tunneling Cluster client is optional	NA
TCSW1	O	Trust Center Swap-out is optional	NA
OTAC1	O	OTA Upgrade Cluster client is optional	NA
OTAS1	O	OTA Upgrade Cluster server is optional	NA

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17

8.8 Smart Energy Application Specific Cluster function capabilities

8.8.1 Basic Cluster

Table 25 – Basic cluster server capabilities

Item number	Item description	Reference	Status	Support
BCS1	Is the Basic Cluster supported as a server?	[R3]	M	Yes 1 – EP#10H
BCS2	Is the ZCLversion attribute supported?		BCS1:M	Yes 1 – EP#10H
BCS3	Is the Powersource attribute supported?		BCS1:M	Yes 1 – EP#10H

Table 26 – Basic cluster client capabilities

Item number	Item description	Reference	Status	Support
BCC1	Is the Basic Cluster supported as a client?	[R3]	O	No

8.8.2 Identify

8.8.3 Alarms

8.8.4 Commissioning

1 **8.8.5 Power Configuration**

2
3

4 **8.8.6 Time Cluster attributes and functions**

5 **Table 27 – Time cluster server capabilities**

Item number	Item description	Reference	Status	Support
TICS1	Is the Time Cluster supported as a server?	[R3]	O	Yes 1 – EP#10H
TICS2	Is the Time attribute supported?		TICS1:M	Yes 1 – EP#10H
TICS3	Is the TimeStatus attribute supported?		TICS1:M	Yes 1 – EP#10H
TICS4	Is the TimeZone attribute supported?		TICS1:O	Yes 1 – EP#10H
TICS5	Is the DstStart attribute supported?		TICS1:O	Yes 1 – EP#10H
TICS6	Is the DstEnd attribute supported?		TICS1:O	Yes 1 – EP#10H
TICS7	Is the DstShift attribute supported?		TICS1:O	Yes 1 – EP#10H
TICS8	Is the StandardTime attribute supported?		TICS1:O	Yes 1 – EP#10H
TICS9	Is the LocalTime attribute supported?		TICS1:O	Yes 1 – EP#10H

6 **Table 28 – Time cluster client capabilities**

Item number	Item description	Reference	Status	Support
TICC1	Is the Time Cluster supported as a client?	[R3]	O	No

7
8

1 **8.8.7 Key Establishment Cluster attributes and functions**

2 **Table 29 – Key Establishment cluster server capabilities**

Item number	Item description	Reference	Status	Support
KECS1	Is the Key Establishment Cluster supported as a server?	[R2]/C.3.1	M	Yes
KECS2	Is the KeyEstablishmentSuite attribute supported?		KECS1:M	Yes
KECS3	Is the reception of Initiate Key Establishment Request command supported?		KECS1:M	Yes
KECS4	Is the reception of Ephemeral Data Request command supported?		KECS1:M	Yes
KECS5	Is the reception of Confirm Key Data Request command supported?		KECS1:M	Yes
KECS6	Is the reception of Terminate Key Establishment command supported?		KECS1:M	Yes
KECS7	Is the generation of Initiate Key Establishment Response command supported?		KECS1:M	Yes
KECS8	Is the generation of Ephemeral Data Response command supported?		KECS1:M	Yes
KECS9	Is the generation of Confirm Key Data Response command supported?		KECS1:M	Yes

3 **Table 30 – Key Establishment cluster client capabilities**

Item number	Item description	Reference	Status	Support
KECC1	Is the Key Establishment Cluster supported as a client?	[R2]/C.3.1	M	Yes
KECC2	Is the KeyEstablishmentSuite attribute supported?		KECC1:M	Yes
KECC3	Is the reception of Initiate Key Establishment Response command supported?		KECC1:M	Yes

Item number	Item description	Reference	Status	Support
KECC4	Is the reception of Ephemeral Data Response command supported?		KECC1:M	Yes
KECC5	Is the reception of Confirm Key Data Response command supported?		KECC1:M	Yes
KECC6	Is the reception of Terminate Key Establishment command supported?		KECC1:M	Yes
KECC7	Is the generation of Initiate Key Establishment Request command supported?		KECC1:M	Yes
KECC8	Is the generation of Ephemeral Data Request command supported?		KECC1:M	Yes
KECC9	Is the generation of Confirm Key Data Request command supported?		KECC1:M	Yes
KECC10	Is the generation of Terminate Key Establishment command supported?		KECC1:M	Yes

1

2 **8.8.8 Demand Response and Load Control Cluster attributes and functions**

3

Table 31 – Demand Response and Load Control cluster server capabilities

Item number	Item description	Reference	Status	Support
DRLCCS1	Is the Demand Response and Load Control Cluster supported as a server?	[R2]/D.2	O	Yes 1 – EP#10H
DRLCCS2	Is the reception of Report Event Status command supported?		DRLCCS1:M	Yes 1 – EP#10H
DRLCCS3	Is the reception of Get Scheduled Events command supported?		DRLCCS1:M	Yes 1 – EP#10H
DRLCCS4	Is the generation of Load Control Event command supported?		DRLCCS1:M	Yes 1 – EP#10H
DRLCCS5	Is the generation of Cancel Load Control Event command supported?		DRLCCS1:M	Yes 1 – EP#10H
DRLCCS6	Is the generation of Cancel All Load Control		DRLCCS1:M	Yes

Item number	Item description	Reference	Status	Support
	Events command supported?			1 – EP#10H

1 **Table 32 – Demand Response and Load Control cluster client capabilities**

Item number	Item description	Reference	Status	Support
DRLCCC1	Is the Demand Response and Load Control Cluster supported as a client?	[R2]/D.2	O	No
DRLCCC2	Is the UtilityEnrolmentGroup attribute supported?		DRLCCC1:M	NA
DRLCCC3	Is the StartRandomizeMinutes attribute supported?		DRLCCC1:M	NA
DRLCCC4	Is the StopRandomizeMinutes attribute supported?		DRLCCC1:M	NA
DRLCCC5	Is the DeviceClassValue attribute supported?		DRLCCC1:M	NA
DRLCCC6	Is the reception of Load Control Event command supported?		DRLCCC1:M	NA
DRLCCC7	Is the reception of Cancel Load Control Event command supported?		DRLCCC1:M	NA
DRLCCC8	Is the reception of Cancel All Load Control Events command supported?		DRLCCC1:M	NA
DRLCCC9	Is the generation of Report Event Status command supported?		DRLCCC1:M	NA
DRLCCC10	Is the generation of Get Scheduled Events command supported?		DRLCCC1:M	NA

2
3

4 **8.8.9 Metering Cluster attributes and functions**

5 **Table 33 – Metering cluster server capabilities**

Item number	Item description	Reference	Status	Support
MECS1	Is the Metering Cluster supported as a server?	[R2]/D.3	O	Yes 1 – EP#10H

Item number	Item description	Reference	Status	Support
MECS2	Is the CurrentSummationDelivered attribute supported?		MECS1:M	Yes 1 – EP#10H
MECS3	Is the CurrentSummationReceived attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS4	Is the CurrentMaxDemandDelivered attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS5	Is the CurrentMaxDemandReceived attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS6	Is the DFTSummation attribute supported?		MECS1:O	No
MECS7	Is the DailyFreezeTime attribute supported?		MECS1:O	No
MECS8	Is the PowerFactor attribute supported?		MECS1:O	No
MECS9	Is the ReadingSnapShotTime attribute supported?		MECS1:O	No
MECS10	Is the CurrentMaxDemandDeliveredTime attribute supported?		MECS1:O	No
MECS11	Is the CurrentMaxDemandReceivedTime attribute supported?		MECS1:O	No
MECS12	Is the DefaultUpdatePeriod attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS13	Is the FastPollUpdatePeriod attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS14	Is the CurrentBlockPeriodConsumptionDelivered attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS15	Is the DailyConsumptionTarget attribute supported?		MECS1:O	No
MECS16	Is the CurrentBlock attribute supported?		MECS1:O	No
MECS17	Is the CurrentTier1SummationDelivered attribute supported?		MECS1:O	Yes 1 – EP#10H
MEC18	Is the CurrentTier1SummationReceived attribute		MECS1:O	Yes

Item number	Item description	Reference	Status	Support
	supported?			1 – EP#10H
MECS19	Is the CurrentTier2SummationDelivered attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS20	Is the CurrentTier2SummationReceived attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS21	Is the CurrentTier3SummationDelivered attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS22	Is the CurrentTier3SummationReceived attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS23	Is the CurrentTier4SummationDelivered attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS24	Is the CurrentTier4SummationReceived attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS25	Is the CurrentTier5SummationDelivered attribute supported?		MECS1:O	No
MECS26	Is the CurrentTier5SummationReceived attribute supported?		MECS1:O	No
MECS27	Is the CurrentTier6SummationDelivered attribute supported?		MECS1:O	No
MECS28	Is the CurrentTier6SummationReceived attribute supported?		MECS1:O	No
MECS29	Is the CurrentTier7SummationDelivered attribute supported?		MECS1:O	No
MECS30	Is the CurrentTier7SummationReceived attribute supported?		MECS1:O	No
MECS31	Is the CurrentTier8SummatioDelivered attribute supported?		MECS1:O	No
MECS32	Is the CurrentTier8SummationReceived attribute supported?		MECS1:O	No
MECS33	Is the CurrentTier9SummationDelivered		MECS1:O	No

Item number	Item description	Reference	Status	Support
	attribute supported?			
MECS34	Is the CurrentTier9SummationReceived attribute supported?		MECS1:O	No
MECS35	Is the CurrentTier10SummationDelivered attribute supported?		MECS1:O	No
MECS36	Is the CurrentTier10SummationReceived attribute supported?		MECS1:O	No
MECS37	Is the CurrentTier11SummationDelivered attribute supported?		MECS1:O	No
MECS38	Is the CurrentTier11SummationReceived attribute supported?		MECS1:O	No
MECS39	Is the CurrentTier12SummationDelivered attribute supported?		MECS1:O	No
MECS40	Is the CurrentTier12SummationReceived attribute supported?		MECS1:O	No
MECS41	Is the CurrentTier13SummationDelivered attribute supported?		MECS1:O	No
MECS42	Is the CurrentTier13SummationReceived attribute supported?		MECS1:O	No
MECS43	Is the CurrentTier14SummationDelivered attribute supported?		MECS1:O	No
MECS44	Is the CurrentTier14SummationReceived attribute supported?		MECS1:O	No
MECS45	Is the CurrentTier15SummationDelivered attribute supported?		MECS1:O	No
MECS46	Is the CurrentTier15SummationReceived attribute supported?		MECS1:O	No
MECS47	Is the Meter Status attribute supported?		MECS1:M	Yes 1 – EP#10H
MECS48	Is the UnitofMeasure attribute supported?		MECS1:M	Yes

Item number	Item description	Reference	Status	Support
				1 – EP#10H
MECS49	Is the Multiplier attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS50	Is the Divisor attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS51	Is the SummationFormatting attribute supported?		MECS1:M	Yes 1 – EP#10H
MECS52	Is the DemandFormatting attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS53	Is the HistoricalConsumptionFormatting attribute supported?		MECS1:O	No
MECS54	Is the MeteringDeviceType attribute supported?		MECS1:M	Yes 1 – EP#10H
MECS54a	Is the MeteringDeviceType: Electric Metering?		MECS54:O.1	Yes 1 – EP#10H
MECS54b	Is the MeteringDeviceType: Gas Metering?		MECS54:O.1	No
MECS54c	Is the MeteringDeviceType: Water Metering?		MECS54:O.1	No
MECS54d	Is the MeteringDeviceType: Pressure Metering?		MECS54:O.1	No
MECS54e	Is the MeteringDeviceType: Heat Metering?		MECS54:O.1	No
MECS54f	Is the MeteringDeviceType: Cooling Metering?		MECS54:O.1	No
MECS55	Is the SiteID attribute supported?		MECS1:O	No
MECS56	Is the MeterSerialNumber attribute supported?		MECS1:O	No
MECS57	Is the InstantaneousDemand attribute supported?		MECS1:O	Yes 1 – EP#10H
MECS58	Is the CurrentDayConsumptionDelivered attribute supported?		MECS1:O	No
MECS59	Is the CurrentDayConsumptionReceived attribute supported?		MECS1:O	No

Item number	Item description	Reference	Status	Support
MECS60	Is the PreviousDayConsumptionDelivered attribute supported?		MECS1:O	No
MECS61	Is the PreviousDayConsumptionReceived attribute supported?		MECS1:O	No
MECS62	Is the CurrentPartialProfileIntervalStartTimeDelivered attribute supported?		MECS1:O	No
MECS63	Is the CurrentPartialProfileIntervalStartTimeReceived attribute supported?		MECS1:O	No
MECS64	Is the CurrentPartialProfileIntervalValueDelivered attribute supported?		MECS1:O	No
MECS65	Is the CurrentPartialProfileIntervalValueReceived attribute supported?		MECS1:O	No
MECS66	Is the MaxNumberOfPeriodsDelivered attribute supported?		MECS1:O	No
MECS67	Is the CurrentDemandDelivered attribute supported?		MECS1:O	No
MECS68	Is the DemandLimit attribute supported?		MECS1:O	No
MECS69	Is the DemandIntegrationPeriod attribute supported?		MECS1:O	No
MECS70	Is the NumberOfDemandSubintervals attribute supported?		MECS1:O	No
MECS71	Is the reception of Get Profile command supported?		MECS1:O	No
MECS72	Is the reception of Request Mirror Response command supported?		MECS1:O	No
MECS73	Is the reception of Mirror Removed command supported?		MECS1:O	No

Item number	Item description	Reference	Status	Support
MECS74	Is the generation of Get Profile Response command supported?		MECS1:O	No
MECS75	Is the generation of Request Mirror command supported?		MECS1:O	No
MECS76	Is the generation of Remove Mirror command supported?		MECS1:O	No
MECS77	Is the ProfileIntervalPeriod attribute supported?		MECS1:O	No
MECS78	Is the IntervalReadReportingPeriod attribute supported?		MECS1:O	No
MECS79	Is the PresetReadingTime attribute supported?		MECS1:O	No
MECS80	Is the VolumePerReport attribute supported?		MECS1:O	No
MECS81	Is the FlowRestriction attribute supported?		MECS1:O	No
MECS82	Is the Supply Status attribute supported?		MECS1:O	No
MECS83	Is the CurrentDayMaxPressure attribute supported?		MECS1:O	No
MECS84	Is the CurrentDayMinPressure attribute supported?		MECS1:O	No
MECS85	Is the PreviousDayMaxPressure attribute supported?		MECS1:O	No
MECS86	Is the PreviousDayMinPressure attribute supported?		MECS1:O	No
MECS87	Is the CurrentDayMaxDemand attribute supported?		MECS1:O	No
MECS88	Is the PreviousDayMaxDemand attribute supported?		MECS1:O	No
MECS89	Is the Meter Status (Gas) attribute supported?		MECS1:O	No
MECS90	Is the Meter Status (Water) attribute supported?		MECS1:O	No

Item number	Item description	Reference	Status	Support
MECS91	Is the RemainingBatteryLife attribute supported?		MECS1:O	No
MECS92	Is the Block Information attribute set supported?		MECS1:O	No
MECS93	Is the CurrentInletEnergyCarrierSummation attribute supported?		MECS54e:M MECS54f:M MECS1:O	No
MECS94	Is the CurrentOutletEnergyCarrierSummation attribute supported?		MECS1:O	No
MECS95	Is the InletTemperature attribute supported?		MECS54e:M MECS54f:M MECS1:O	No
MECS96	Is the OutletTemperature attribute supported?		MECS54e:M MECS54f:M MECS1:O	No
MECS97	Is the ControlTemperature attribute supported?		MECS1:O	No
MECS98	Is the CurrentInletEnergyCarrierDemand attribute supported?		MECS1:O	No
MECS99	Is the CurrentOutletEnergyCarrierDemand attribute supported?		MECS1:O	No
MECS100	Is the EnergyCarrierUnitOfMeasure attribute supported?		MECS54e:M MECS54f:M MECS1:O	No
MECS101	Is the EnergyCarrierSummationFormatting attribute supported?		MECS93:M MECS94:M	NA
MECS102	Is the EnergyCarrierDemandFormatting attribute supported?		MECS98:M MECS99:M MECS107:M MECS108:M MECS109:M MECS110:M MECS111:M MECS112:M	NA
MECS103	Is the TemperatureUnitOfMeasure attribute supported?		MECS54e:M MECS54f:M	NA

Item number	Item description	Reference	Status	Support
MECS104	Is the TemperatureFormatting attribute supported?		MECS54e:M MECS54f:M	NA
MECS105	Is the CurrentMonthMaxDemand attribute supported?		MECS1:O	No
MECS106	Is the CurrentYearMaxDemand attribute supported?		MECS1:O	No
MECS107	Is the CurrentDayMaxEnergyCarrierDemand attribute supported?		MECS1:O	No
MECS108	Is the PreviousDayMaxEnergyCarrierDemand attribute supported?		MECS1:O	No
MECS109	Is the CurrentMonthMaxEnergyCarrierDemand attribute supported?		MECS1:O	No
MECS110	Is the CurrentMonthMinEnergyCarrierDemand attribute supported?		MECS1:O	No
MECS111	Is the CurrentYearMaxEnergyCarrierDemand attribute supported?		MECS1:O	No
MECS112	Is the CurrentYearMinEnergyCarrierDemand attribute supported?		MECS1:O	No
MECS113	Is the HoursInOperation attribute supported?		MECS54e:M MECS54f:M	NA
MECS114	Is the HoursInFault attribute supported?		MECS1:O	No
MECS115	Is the Generic AlarmMask attribute supported?		MECS1:O	No
MECS116	Is the Electricity AlarmMask attribute supported?		MECS1:O	No
MECS117	Is the GenericFlow/Pressure AlarmMask attribute supported?		MECS1:O	No
MECS118	Is the Water Specific AlarmMask attribute supported?		MECS1:O	No
MECS119	Is the Heating Specific AlarmMask attribute supported?		MECS1:O	No

Item number	Item description	Reference	Status	Support
MECS120	Is the Cooling Specific AlarmMask attribute supported?		MECS1:O	No
MECS121	Is the Gas Specific AlarmMask attribute supported?		MECS1:O	No
MECS122	Is the reception of Request Fast Poll Mode command supported?		MECS1:O	Yes 1 – EP#10H
MECS123	Is the generation of Request Fast Poll Mode Response supported?		MECS1:O	Yes 1 – EP#10H
MECS124	Is the Mapping of the Status Attribute (Electricity) supported?	[R2]/D.3.2.2.3.1 Table D.16	MECS54a:M	Yes 1 – EP#10H
MECS125	Is the Meter Status Attribute (Gas) mapping supported?	[R2]/D.3.2.2.3.1 Table D.17	MECS54b:M	NA
MECS126	Is the Meter Status Attribute (Water) mapping supported?	[R2]/D.3.2.2.3.1 Table D.18	MECS54c:M	NA
MECS127	RESERVED			NA
MECS128	Is the Meter Status Attribute (Heat and Cooling) mapping?	[R2]/D.3.2.2.3.1 Table D.19	MECS54e:M MECS54f:M	NA
MECS129	RESERVED			NA
MECS130	Does the device generate fragmented Get Profile Response commands?		MECS74:O	NA

1

Table 34 – Metering cluster client capabilities

Item number	Item description	Reference	Status	Support
MECC1	Is the Metering Cluster supported as a client?	[R2]/D.3	O	No
MECC2	Is the reception of Get Profile Response command supported?		MECC1:O	NA
MECC3	Is the reception of Request Mirror command supported?		MECC1:O	NA
MECC4	Is the reception of Remove Mirror command		MECC1:O	NA

Item number	Item description	Reference	Status	Support
	supported?			
MECC5	Is the generation of Get Profile command supported?		MECC1:O	NA
MECC6	Is the generation of Request Mirror Response command supported?		MECC1:O	NA
MECC7	Is the generation of Mirror Removed command supported?		MECC1:O	NA
MECC8	Is the reception of Request Fast Poll Mode Response command supported?		MECC1:O	NA
MECC9	Is the generation of Request Fast Poll Mode command supported?		MECC1:O	NA
MECC10	Does the device support reception of fragmented Get Profile Response commands?		MECC5:M	NA

1
2
3
4

8.8.10 Price Cluster attributes and functions

Table 35 – Price cluster server capabilities

Item number	Item description	Reference	Status	Support
PCS1	Is the Price Cluster supported as a server?	[R2]/D.4	O	Yes 1 – EP#10H
PCS2	Is the Tier1PriceLabel attribute supported?		PCS1:O	Yes 1 – EP#10H
PCS3	Is the Tier2PriceLabel attribute supported?		PCS1:O	Yes 1 – EP#10H
PCS4	Is the Tier3PriceLabel attribute supported?		PCS1:O	Yes 1 – EP#10H
PCS5	Is the Tier4PriceLabel attribute supported?		PCS1:O	Yes 1 – EP#10H
PCS6	Is the Tier5PriceLabel attribute supported?		PCS1:O	No

Item number	Item description	Reference	Status	Support
PCS7	Is the Tier6PriceLabel attribute supported?		PCS1:O	No
PCS8	Is the reception of Get Current Price command supported?		PCS1:M	Yes 1 – EP#10H
PCS9	Is the reception of Get Scheduled Prices command supported?		PCS1:O	Yes 1 – EP#10H
PCS10	Is the generation of Publish Price command supported?		PCS1:M	No
PCS11	Is the Tier7PriceLabel attribute supported?		PCS1:O	No
PCS12	Is the Tier8PriceLabel attribute supported?		PCS1:O	No
PCS13	Is the Tier9PriceLabel attribute supported?		PCS1:O	No
PCS14	Is the Tier10PriceLabel attribute supported?		PCS1:O	No
PCS15	Is the Tier11PriceLabel attribute supported?		PCS1:O	No
PCS16	Is the Tier12PriceLabel attribute supported?		PCS1:O	No
PCS17	Is the Tier13PriceLabel attribute supported?		PCS1:O	No
PCS18	Is the Tier14PriceLabel attribute supported?		PCS1:O	No
PCS19	Is the Tier15PriceLabel attribute supported?		PCS1:O	No
PCS20	Is the Block Threshold attribute set supported?		PCS1:O	No
PCS25	Is the reception of Price Acknowledgement command supported?		PCS1:O	Yes 1 – EP#10H
PCS26	Is the generation of Publish Block Period command supported?		PCS1:O	No
PCS27	Is the reception of Get Block Period(s) command support?		PCS1:O	No
PCS28	Is the Commodity Type (server) attribute supported?		PCS1:O	No
PCS29	Is the Standing Charge attribute supported?		PCS1:O	No

Item number	Item description	Reference	Status	Support
PCS30	Is the Block Price Information attribute set supported?		PCS1:O	No

1

2

Table 36 – Price cluster client capabilities

Item number	Item description	Reference	Status	Support
PCC1	Is the Price Cluster supported as a client?	[R2]/D.4	O	No
PCC2	Is the reception of Publish Price command supported?		PCC1:M	NA
PCC3	Is the generation of Get Current Price command supported?		PCC1:M	NA
PCC4	Is the generation of Get Scheduled Prices command supported?		PCC1:O	NA
PCC5	Is the PriceIncreaseRandomizeMinutes attribute supported?		PCC1:O	NA
PCC6	Is the PriceDecreaseRandomizeMinutes attribute supported?		PCC1:O	NA
PCC7	Is the Commodity Type (client) attribute supported?		PCC1:O	NA
PCC8	Is the generation of Price Acknowledgement command supported?		PCC1:O	NA
PCC9	Is the reception of Publish Block Period command supported?		PCC1:O	NA
PCC10	Is the generation of Get Block Period(s) command supported?		PCC1:O	NA
PCC11	Is the Block Tariffs TOU charging behavior supported?	[R2]/D.4.4.3.1	PCC10:M	NA
PCC12	Is the Block Tariffs Block Charging behavior supported?	[R2]/D.4.4.3.2	PCC10:M	NA

Item number	Item description	Reference	Status	Support
PCC13	Is the Block Tariffs Block/TOU Combination Charging supported?	[R2]/D.4.4.3.3	PCC10:M	NA
PCC14	Is the Block Tariffs guideline for extended non-communication supported?	[R2]/D.4.4.3.4	PCC10:O	NA
PCC15	Is the Block Tariffs guideline for meter installation or swap-out supported?	[R2]/D.4.4.3.4	PCC10:O	NA

1
2
3
4

8.8.11 Messaging Cluster attributes and functions

Table 37 – Messaging cluster server capabilities

Item number	Item description	Reference	Status	Support
MCS1	Is the Messaging Cluster supported as a server?	[R2]/D.5	O	Yes 1 – EP#10H
MCS2	Is the reception of Get Last Message command supported?		MCS1:M	Yes 1 – EP#10H
MCS2	Is the reception of Message Confirmation command supported?		MCS1:M	Yes 1 – EP#10H
MCS3	Is the generation of Display Message command supported?		MCS1:M	Yes 1 – EP#10H
MCS4	Is the generation of Cancel Message command supported?		MCS1:M	Yes 1 – EP#10H

5

Table 38 – Messaging cluster client capabilities

Item number	Item description	Reference	Status	Support
MCC1	Is the Messaging Cluster supported as a client?	[R2]/D.5	M	No
MCC2	Is the reception of Display Message command supported?		MCC1:M	NA
MCC3	Is the reception of Cancel Message command		MCC1:M	NA

Item number	Item description	Reference	Status	Support
	supported?			
MCC4	Is the generation of Get Last Message command supported?		MCC1:M	NA
MCC5	Is the generation of Message Confirmation command supported?		MCC1:M	NA

1

2 **8.8.12 Tunneling Cluster attributes and functions**

3

Table 39 – Tunneling cluster server capabilities

Item number	Item description	Reference	Status	Support
TUS1	Is the Tunneling Cluster supported as a server?	[R2]/D.6	O	No
TUS2	Is the reception of RequestTunnel command supported?	[R2]/D.6.2.4	TUS1:M	NA
TUS3	Is the reception of CloseTunnel command supported?	[R2]/D.6.2.4	TUS1:M	NA
TUS4	Is the reception of TransferData command supported?	[R2]/D.6.2.4	TUS1:M	NA
TUS5	Is the reception of TransferDataError command supported?	[R2]/D.6.2.4	TUS1:M	NA
TUS6	Is the reception of AckTransferData command supported?	[R2]/D.6.2.4	TUS1:O	NA
TUS7	Is the reception of ReadyData command supported?	[R2]/D.6.2.4	TUS1:O	NA
TUS8	Is the generation of RequestTunnelResponse command supported?	[R2]/D.6.2.5	TUS1:M	NA
TUS9	Is the generation of TransferData command supported?	[R2]/D.6.2.5	TUS1:M	NA
TUS10	Is the generation of TransferDataError command supported?	[R2]/D.6.2.5	TUS1:M	NA

Item number	Item description	Reference	Status	Support
TUS11	Is the generation of AckTransferData command supported?	[R2]/D.6.2.5	TUS1:O	NA
TUS12	Is the generation of ReadyData command supported?	[R2]/D.6.2.5	TUS1:O	NA

1

2

Table 40 – Tunneling cluster client capabilities

Item number	Item description	Reference	Status	Support
TUC1	Is the Tunneling Cluster supported as a client?	[R2]/D.6	O	No
TUC2	Is the reception of RequestTunnelResponse command supported?	[R2]/D.6.3.3	TUC1:M	NA
TUC3	Is the reception of TransferData command supported?	[R2]/D.6.3.3	TUC1:M	NA
TUC4	Is the reception of TransferDataError command supported?	[R2]/D.6.3.3	TUC1:M	NA
TUC5	Is the reception of AckTransferData command supported?	[R2]/D.6.3.3	TUC1:O	NA
TUC6	Is the generation of ReadyData command supported?	[R2]/D.6.3.3	TUC1:O	NA
TUC7	Is the generation of RequestTunnel command supported?	[R2]/D.6.3.4	TUC1:M	NA
TUC8	Is the generation of CloseTunnel command supported?	[R2]/D.6.3.4	TUC1:M	NA
TUC9	Is the generation of TransferData command supported?	[R2]/D.6.3.4	TUC1:M	NA
TUC10	Is the generation of TransferDataError command supported?	[R2]/D.6.3.4	TUC1:M	NA
TUC11	Is the generation of AckTransferData command supported?	[R2]/D.6.3.4	TUC1:O	NA

Item number	Item description	Reference	Status	Support
TUC12	Is the generation of ReadyData command supported?	[R2]/D.6.3.4	TUC1:O	NA

1

2 **8.8.13 Prepayment Cluster attributes and functions**

3

Table 41 – Prepayment cluster server capabilities

Item number	Item description	Reference	Status	Support
PPCS1	Is the Prepayment Cluster supported as a server?	[R2]/D.7	O	No
PPCS2	Is the reception of Select Available Emergency Credit command supported?	[R2]/D.7.2.3	PPCS1:O	NA
PPCS3	Is the reception of Change Supply command supported?	[R2]/D.7.2.3	PPCS1:O	NA
PPCS4	Is the generation of Supply Status Response command supported?	[R2]/D.7.2.4	PPCS1:O	NA
PPCS7	Is the Payment Control attribute supported?	[R2]/D.7.2.2.1	PPCS1:M	NA
PPCS8	Is the Credit Remaining attribute supported?	[R2]/D.7.2.2.1	PPCS1:O	NA
PPCS9	Is the Emergency Credit Remaining attribute supported?	[R2]/D.7.2.2.1	PPCS1:O	NA
PPCS10	Is the Credit Status attribute supported?	[R2]/D.7.2.2.1	PPCS1:O	NA
PPCS11	Are the Top up Date/Time attributes supported? If so, list supported attributes #1-5.	[R2]/D.7.2.2.2	PPCS1:O	NA
PPCS12	Are the Top up Amount attributes supported? If so, list supported attributes #1-5.	[R2]/D.7.2.2.2	PPCS1:O	NA
PPCS13	Are the Originating Device attributes supported? If so, list supported attributes #1-5.	[R2]/D.7.2.2.2	PPCS1:O	NA
PPCS14	Is the Fuel Debt Remaining attribute supported?	[R2]/D.7.2.2.3	PPCS1:O	NA

Item number	Item description	Reference	Status	Support
PPCS15	Is the Fuel Debt Recovery Rate attribute supported?	[R2]/D.7.2.2.3	PPCS1:O	NA
PPCS16	Is the Fuel Debt Recovery Period attribute supported?	[R2]/D.7.2.2.3	PPCS1:O	NA
PPCS17	Is the Non Fuel Debt Remaining attribute supported?	[R2]/D.7.2.2.3	PPCS1:O	NA
PPCS18	Is the Non Fuel Debt Recovery Rate attribute supported?	[R2]/D.7.2.2.3	PPCS1:O	NA
PPCS19	Is the Non Fuel Debt Recovery Period attribute supported?	[R2]/D.7.2.2.3	PPCS1:O	NA
PPCS20	Is the Proposed Change Provider ID attribute supported?	[R2]/D.7.2.2.4	PPCS1:O	NA
PPCS21	Is the Proposed Change Implementation Time attribute supported?	[R2]/D.7.2.2.4	PPCS1:O	NA
PPCS22	Is the Proposed Change Supply Status attribute supported?	[R2]/D.7.2.2.4	PPCS1:O	NA
PPCS23	Is the Delayed Supply Interrupt – Value Remaining attribute supported?	[R2]/D.7.2.2.4	PPCS1:O	NA
PPCS24	Is the Delayed Supply Interrupt – Value Type attribute supported?	[R2]/D.7.2.2.4	PPCS1:O	NA

1

2

Table 42 – Prepayment cluster client capabilities

Item number	Item description	Reference	Status	Support
PPCC1	Is the Prepayment Cluster supported as a client?	[R2]/D.7	O	No
PPCC2	Is the generation of Select Available Emergency Credit command supported?	[R2]/D.7.3.4	PPCC1:O	NA
PPCC3	Is the generation of Change Supply command supported?	[R2]/D.7.3.4	PPCC1:O	NA

Item number	Item description	Reference	Status	Support
PPCC4	Is the reception of Supply Status Response command supported?	[R2]/D.7.3.3	PPCC1:O	NA

1

2 **8.8.14 Trust Center Swap-out**

3

Table 43 – Trust Center Swap-out capabilities

Item number	Item description	Reference	Status	Support
TCSW1	Is the device a Trust Center supporting Trust Center Swap-out?	[R2]/5.4.2.2.3	O	No
TCSW2	Is the generation of Trust Center keep-alive command supported?		TCSW1:M FDT1:M FDT2:M	NA
TCSW3	Is the backup of the Extended PAN ID to an off-chip device supported?		TCSW1:M FDT1:M	NA
TCSW4	Is the backup of the registered device EUI-64 to an off-chip device supported?		TCSW1:M FDT1:M	NA
TCSW5	Is the backup of the registered device Install Code to an off-chip device supported?		TCSW1:M FDT1:M	NA
TCSW6	Is the backup of the registered device hashed CBKE derived link key to an off-chip device supported?		TCSW1:M FDT1:M	NA
TCSW7	Is the restore of the Extended PAN ID from an off-chip device supported?		TCSW1:M FDT1:M	NA
TCSW8	Is the restore of the registered device EUI-64 from an off-chip device supported?		TCSW1:M FDT1:M	NA
TCSW9	Is the restore of the registered device Install Code from an off-chip device supported?		TCSW1:M FDT1:M	NA

Item number	Item description	Reference	Status	Support
TCSW10	Is the restore of the registered device hashed CBKE derived link key from an off-chip device supported?		TCSW1:M FDT1:M	NA
TCSW11	Is the discovery of the new Trust Center based on the Extended PAN ID supported?		TCSW1:M FDT2:M	NA
TCSW12	Is the rejoin using the CBKE derived link key supported?		TCSW1:M FDT2:M	NA
TCSW13	Is the Reconnection of device supported?		FDT1:M FDT2:M FDT3:M	NA
TCSW14	Does the device support the Trust Center Swap-Out parameters?	[R2] 5.4.2.2.3.7	TCSW1:M FDT1:M	NA

1

2 **8.8.15 Multiple ESI**

3

Table 44 – Multiple ESI Client capabilities

Item number	Item description	Reference	Status	Support
MESC1	Is Multiple ESI supported?	[R2]/5.7	O	No
MESC2	Is the discovery of all ESIs in a HAN supported?		MESC1:M	NA
MESC3	Is the generation of bindings on discovered ESIs supported?		MESC1:M	NA
MESC4	Is determination of the authoritative ESI supported?		MESC1:M	NA
MESC5	Is processing of events from multiple ESIs supported?		MESC1:M	NA
MESC6	Is resolution of conflicting events received		MESC1:M	NA

Item number	Item description	Reference	Status	Support
	from multiple ESIs supported?			
MESC7	Is the notification message for an event sent to at least one ESI that sent the event?		MESC1:M	NA
MESC8	Is the event processing based on the authoritative time?		MESC1:M	NA

1
2

Table 45 – Multiple ESI Server capabilities

Item number	Item description	Reference	Status	Support
MESS1	Is Multiple ESI supported?	[R2]/5.7	O	Yes 1 – EP#10H
MESS2	Is the <i>TimeStatus</i> attribute supported?		MESS1:M	Yes 1 – EP#10H
MESS3	Is the <i>LastSynchronizedTime</i> attribute supported?		MESS1:M	Yes 1 – EP#10H
MESS4	Is the <i>ValidUntilTime</i> attribute supported?		MESS1:M	Yes 1 – EP#10H

3
4

8.8.16 OTA Upgrade Cluster attributes and functions

5

Table 46 – OTA Upgrade cluster server capabilities

Item number	Item description	Reference	Status	Support
OTAS1	Is the OTA Upgrade Cluster supported as a server?	[R9]	O	No

6
7

Table 47 – OTA Upgrade cluster client capabilities

Item number	Item description	Reference	Status	Support
OTAC1	Is the OTA Upgrade Cluster supported as a client?	[R9]	O	No

8

1 If supporting OTA upgrade cluster client or server, need to complete OTA Upgrade Cluster PICS
2 document in addition to this document for certification.


3

4 **8.8.17 Support on Non SE clusters**

5

6 List in the below section all non SE clusters supported on the submitted product:

7



1